



TOOL FEATURES

- Suitable for SCRAIL® ROOFLOC® with or without washer
- Easy rear loading magazine
- Special pads avoid scratches on the roof
- Wide contact area for perfect processing

SCRAIL® ROOFLOC®

- Two times faster than collated screws
- Available in all colors upon request
- Collated plastic sheet SCRAIL® strips eliminate fastener waste
- FasCoat® good for exterior applications
- Leak-proof EPDM washer
- Avoids metal shavings



CONTACT & SERVICE

Our sales team
is available at:

P +39 051 6018226
fasco@fasco-tools.com
www.fasco-tools.com

DESCRIPTION

The SCRAIL® ROOFLOC® System was developed by BECK for the quick and efficient installation of trapezoidal sheet metal roofs and façades. The resulting increase in performance is around 100 % and more. The SCRAIL® ROOFLOC® is pneumatically driven with the ROOFLOC® installation tool and can be completely unscrewed for repair work.

APPLICATIONS

- For attaching metal roof to wood
- For attaching metal siding to wood

HANDLING

1. Load fastener from the back into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

| Height | Width |
|------------|-----------|
| 375 mm | 130 mm |
| 14.76 inch | 5.12 inch |
| Length | Weight |
| 415 mm | 4,13 kg |
| 16.34 inch | 9.10 lbs |

Pressure

7 - 8 bar | 100 - 120 psi

Air consumption per shot

1.86 L. | 0.066 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

| | SCRAIL® ROOFLOC® |
|-----------------------|-----------------------------------|
| Diameter | 3,80 4,20 mm 0.148 0.165" |
| Length | 37 63 75 mm 1 ½ 2 ½ 3" |
| Head | 10 mm 0.400" |
| Drive | HEX-Key ¼" |
| Thread Type | patented SteelThread |
| Collation Type | 0° Plastic Sheet Strip |
| Capacity | 30 |

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 101.00 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 94.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.63 m/s²

ACTUATION & LOADING

Actuation System: Single shot
Loading: Rear Loading

FURTHER INFORMATION

EPDM washer

- Cold and heat resistant (-40°C to +120°C = -40°F to +250°F)
Superior resistance to UV (ultraviolet)-radiation*
* According to EPDM Roofing Association
- Leak-proof system according to VHT test report PB-833_5-16-Beck-170329, dated 29.3.2017

